

SECTION PD

MODIFICATION NOTICE:
Service Data and Specifications have been changed.

CONTENTS

SERVICE DATA AND SPECIFICATIONS (SDS)	4002	Final Drive.....	4002
---	------	------------------	------

GENERAL SPECIFICATIONS

Body type	Wagon									
Engine	TB45E		TB48DE		ZD30DDTi		TD42			
Transmission	5M/T			5A/T	5M/T	4A/T	5M/T			
Front final drive	Standard									
	H233B									
	2-pinion									
Gear ratio	4.111		4.375	3.545		4.111	4.375		4.111	
Number of teeth (Drive gear/drive pinion)	37/9		35/8	39/11		37/9	35/8		37/9	
Oil capacity (Approx.) ℓ (Imp pt)	5.4 (9-1/2)									
Rear final drive [Grade]	Standard	Optional	Standard	Optional	Standard	Optional	Standard	Optional	Standard	Standard
	H233B		H260		H233B		H233B			
	4-pinion	LSD	Diff. lock	4-pinion	Diff. lock	4-pinion	Diff. lock	LSD	Diff. lock	4-pinion
Gear ratio	4.111		4.375		3.545		4.111		4.375	4.111
Number of teeth (Drive gear/drive pinion)	37/9		35/8		39/11		37/9		35/8	37/9
Oil capacity (Approx.) ℓ (Imp pt)	2.4 (4-1/4)	2.1 (3-3/4)	3.0 (5-1/4)	4.7 (8-1/4)	3.7 (6-1/2)	2.4 (4-1/4)	3.0 (5-1/4)	2.1 (3-3/4)	3.0 (5-1/4)	2.4 (4-1/4)

Final Drive

SERVICE DATA AND SPECIFICATIONS (SDS)

Final Drive (Cont'd)

Body type	Hardtop				
Engine	TB45E	ZD30DDTi			
Transmission	5M/T	5M/T	4A/T		
Front final drive	Standard				
	H233B				
	2-pinion				
Gear ratio	4.111		4.375		
Number of teeth (Drive gear/drive pinion)	37/9		35/8		
Oil capacity (Approx.) ℓ (Imp pt)	5.4 (9-1/2)				
Rear final drive [Grade]	Standard	Optional	Standard	Optional	Standard
	H233B				
	4-pinion	Diff. lock	LSD	Diff. lock	Diff. lock
Gear ratio	4.111		4.375		
Number of teeth (Drive gear/drive pinion)	37/9		35/8		
Oil capacity (Approx.) ℓ (Imp pt)	2.4 (4-1/4)	3.0 (5-1/4)	2.1 (3-3/4)	3.0 (5-1/4)	3.0 (5-1/4)